



Digital ORP Sensor, PEEK, Insertion

Produktnr: DRD2P5.99
SEK Pris: Kontakta oss
Inget leveransdatum anges

The smart choice for accurate and reliable online process ORP measurement

General Purpose Online Process ORP Sensor with Integrated Digital Electronics for "Plug and Play" with Hach Digital SC Controllers - Platinum ORP Electrode, PEEK Housing, Insertion Mount, 10 m Cable

Exceptional Performance with the Differential Electrode Measurement Technique

This field-proven technique uses three electrodes instead of the two normally used in conventional pH sensors. Process and reference electrodes measure the pH differentially with respect to a third ground electrode. The end result is unsurpassed measurement accuracy, reduced reference junction potential, and elimination of sensor ground loops. These sensors provide greater reliability, resulting in less downtime and maintenance.

Lower Maintenance Needs with the Double Junction Salt Bridge

The double junction salt bridge creates a barrier to contamination which minimises the dilution of the internal standard cell solution. The result is lower maintenance needs and a longer time period between calibrations.

Extended Working Life with the Replaceable Salt Bridge/Protector

The unique, replaceable salt bridge holds an extraordinary volume of buffer to extend the working life of the sensor by protecting the reference electrode from harsh process conditions. The salt bridge simply threads onto the end of the sensor if replacement is needed.

Reliability with Built-in Encapsulated Preamp

Encapsulated construction protects the sensor's built-in preamp from moisture and humidity, ensuring reliable sensor operation. The preamp in the pHD analogue sensor produces a strong signal, enabling the sensor to be located up to 1000 m (3280 ft.) from the analyser.

Innovative Technology

The former GLI, now a Hach Company brand, invented the Differential Electrode Technique for pH measurement in 1970. The pHD sensor series takes this field-proven technology to a new level.

Specifikationer

Arbetsstemperatur : -5 to 70 °C (23 to 158 °F) pHD and ORP

Before initial pH calibration, calibrate the temperature measurement when the sensor is in water or buffer which is at approximately the same temperature as the pH buffers.

Body Material: PEEK
Compliance: Hazardous location, Maritime, CE
Elektrodmateriäl: Platinum
Elektrodtyp: General Purpose
Garanti : 24 månader

Givartyp:	Digital
Kabelanslutning :	Digital
Kabellängd:	10 m
Material:	PEEK
Mätområde:	-1500 to +1500 mV ORP
Monteringsform:	Insertion
Temperaturnoggrannhet:	± 0.5 °C (± 0.9 °F)