



Amtax inter2

Produktnr:

LPV397.99.01000 Farligt

UTGÅNGEN ARTIKEL

Den här artikeln är inte längre tillgänglig.



Amtax inter2 - the ISO compliant NH₄ analyser for in-house measurement

High-precision process photometer for the measurement of the ammonium concentration to optimise nitrification and outflow monitoring. Based on the indophenol blue method according EN ISO 11732.

The principle of intermittent operation guarantees rapidly measured values and economical consumption. Ideally supplied by the sample preparation with in situ filtration.

High accuracy, high precision

Fast measured values - every 5 or 10 minutes

For automated nitrogen elimination

EN ISO 11732 compliant

Small reagents and spare parts consumption

Specifikationer

Antal kanaler:	1
Dimension (H x B x D):	1190 mm x 550 mm x 390 mm
Display :	Graphics monitor with curve display
Garanti :	24 månader
Gränssnitt:	Service Interface: RS 232, No Bus connection
Kalibreringsmetod :	Automatic at selectable intervals
Kommunikationsmöjligheter:	Ingen
Mätintervall:	5 or 10 minutes (choice on contin. sample supply)
Matningskrav (Hz):	50 Hz
Matningskrav (Spänning):	230 V AC
Mätområde:	0,1 - 20 mg/L NH ₄ -N
Mätprincip:	Indophenol blue method, derived from DIN 38406 E5
Noggrannhet:	± 2 % +0.02 of the measured value
Omgivningstemperatur:	5 - 40 °C
Provtagningsalternativ:	1 channel continuous

Reagensförsörjning:	12 month zero and standard solution
Reläer:	1 A 2 Relay contacts, 24 V, floating
Serviceintervall:	6 månader
Standard accessories:	Auto-cleaning facility, data logger
Strömutgång:	0/4 to 20 mA max. 500 Ω ; 2 current putputs
Underhållskrav:	1 h/week
Vikt :	42 kg (without reagents)