



EZ1009 Chromium Cr(VI) Analyser

Produktnr: EZ1009.XXXXXXXX

SEK Pris: Kontakta oss

Online colorimetric analysis of dissolved Chromium Cr(VI) in water

EZ1000 Chromium Cr(VI) Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low $\mu g/L$ range.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator invervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Chromium Cr(VI) Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Specifikationer

Analoga utgångar: Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)

Antal provströmmar: 1, 2, 4, or 8

Automatisk rengöring: Ja

Certifieringar: CE compliant / ETL certified

Cykeltid: 10 min (dilution + 5 min)

Demineralised water: For rinsing / dilution

Detektionsgräns: $\leq 1 \mu g/L$

Digital outputs: Optional: Modbus (TCP/IP, RS485)

Dimension (H x B x D): 690 mm x 465 mm x 330 mm

Dränering: Atmospheric pressure, vented, min. Ø 32 mm

Earth connection: Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²

Garanti: 24 månader

Instrument air: Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air

Kalibrering: Automatic, 2-point; frequency freely programmable

Larm: 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts

Material: Hinged part: Thermoform ABS, door: PMMA

Wall section: Galvanised steel, powder coated

Mätmetod: Colorimetric measurement at 546 nm using diphenylcarbazide method, conform with standard

method APHA 3500-Cr (B)

Matningsspänning: 100 - 240 VAC, 50/60 Hz

Max. power consumption: 120 VA

Mätområde: $5 - 500 \mu g/L Cr(VI)$

Optional:

1 - 50 μ g/L Cr(VI)

2 - 125 μg/L Cr(VI)

2.5 - 250 µg/L Cr(VI)

0.08 - 2 mg/L Cr(VI) (with internal dilution)

0.16 - 4 mg/L Cr(VI) (with internal dilution)

0.5 - 50 mg/L Cr(VI) (with internal dilution)

Modell: EZ1009

Omgivningstemperatur: $10 - 30 \text{ °C} \pm 4 \text{ °C}$ deviation at 5 - 95% relative humidity (non-condensing)

Parameter: Chromium Cr(VI), dissolved
Pausläge: 100 - 240 VAC, 50/60 Hz

Precision: Better than 2% full scale range for standard test solutions

Prov: tryck: By external overflow vessel

Provflödeshastighet: 100 - 300 mL/min

Provkvalitet: Maximum particle size 100 μ m, < 0.1 g/L; Turbidity < 50 NTU

Provtemperatur: 10 - 30 °C

Reagent Requirements: Keep between 10 - 30 °C

Skyddsklass: Analyser cabinet: IP44 / Panel PC: IP65

Störningar: Iron (III), Mercury > 200 mg/L, Molybdenum > 200 mg/L, Vanadium (V) > 5 mg/L.

Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.

Vad ingår i leveransen: EZ1009 Chromium Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting

Brackets, 1 x empty 2.5L Glass Reagent Container with Fittings (for Colour) and 1 x empty 5L

Reagent Container with Fittings (for Buffer Solution)

Validation: Automatic; frequency freely programmable

Vikt: 25 kg

Vad finns i förpackningen $EZ1009\ Chromium\ Analyser,\ Instruction\ Manual,\ 1\ x\ Double\ Bit\ Door\ Key,\ 1\ x\ Mounting\ Brackets,\ 1\ x\ empty\ 2.5L\ Glass\ Reagent\ Container$ with Fittings (for Colour) and 1 x empty 5L Reagent Container with Fittings (for Buffer Solution) Product details pdf footer