

Sension+ 9655 Fluorid jonselektiv elektrod (ISE) - endast sensor

Produktnr: **LZW9655.97.0002**

SEK Pris: Kontakta oss
Inget leveransdatum anges

Sension+ 9655 is a half-cell (reference not integrated) fluoride ion selective electrode (ISE) with an epoxy body and non-replaceable crystalline membrane selective to fluoride ions in solution. It is recommended for use with the Sension+ 5044 reference electrode. The 9655 has a fixed 1 meter cable and BNC connector for laboratory use with the Hach Sension+ MM374 Multimeter. The 9655 is ideal for measuring fluoride concentrations in drinking water, wastewater and general water quality applications.

Requires virtually no maintenance
The solid-state sensor design allows for DRY storage of the ISE without a shelf life or membrane replacement.

Provides fast, stable, and accurate response in a variety of sample types

Specifikationer

Dimension (D x L):	12 mm x 120 mm
Elektrolyt:	-
Garanti :	6 månader
Givar koppling:	-
Givartyp:	Laboratory Half-Cell ISE
ISA-krav :	258999
Kabellängd:	1 m
Kontakt:	BNC Connector
Längd:	120 mm
Material:	Sensor Body: Epoxy
Mätområde:	0.02 mg/L - 20,000 mg/L F^-
Parameter:	Fluoride
Specialfunktioner:	Dry storage & fast response time. No replacement membranes.
Temperaturområde :	5 - 50 °C
Termistor:	-
Typ:	Lab ISE, referens behövs
Vad ingår i leveransen:	Inkluderar: Sension+ 9655 Fluoride ISE (halvcell) och grundläggande användarhandbok.

Vad finns i förpackningen

Inkluderar: Sension+ 9655 Fluoride ISE (halvcell) och grundläggande användarhandbok.

Obligatoriska tillbehör

- Fluorid jonstyrkejustering (ISA) pulverkuddar, pk/100 (Item 258999)
- Sension+ elektrolytlösning, 0,1 M, för ISE-elektroder, 125 mL (Item LZW9901.99)