

1200-S sc Digital pH sensor for SC controller

Produktnr: **LXV426.99.10001**

SEK Pris: Kontakta oss
Skickas inom 1 vecka

1200-S sc: combined digital electrode for pH

Immersion probe for wastewater with integrated AD electronics and exchangeable pH combination electrode, with 10 m cable

This instrument connects to Claros, Hach’s innovative Water Intelligence System, enabling you to seamlessly connect and manage instruments, data, and process – anywhere, anytime. The result is greater confidence in your data and improved efficiency in your operations. To unlock the full potential of Claros, insist on Claros Enabled instruments.

High-quality combined electrode

Electrode with perforated membrane and gel

electrolyte

Low user maintenance

Plug and play with SC controllers

Specifikationer

Diameter:	42 mm
Flöde:	Max. 4 m/s
Fuktade material:	Stainless steel, Polyurethane, PPS
Garanti :	24 månader
Kabellängd:	10 m hard wired, polyurethane
Kalibreringsmetod :	One or two point standard buffer solution (automatic), One or two point comparative measurement
Kapslingsklass:	IP68
Kommunikation:	MODBUS
Lagringsförhållanden:	-20 °C - 60 °C
Längd:	504 mm
Material:	Sensor Body: Stainless steel Sensor Cable: Polyurethane Other: PPS

Mätområde:	0 - 14 pH
Monteringsform:	Immersed pipe, chain
Noggrannhet:	± 0,2 °C
Omgivningstemperatur:	-5 - 50 °C
Parameter:	pH
Repeterbarhet:	± 0.5 %
Responstid T90:	< 2 min temperature
Temperaturgivare:	PT100
Tryckområde:	2 bar
Vikt :	< 1 kg

Obligatoriska tillbehör

- SC1000 probmodul för 4 givare, 4x 4 - 20 mA UT, relä, 110 - 240 VAC, EU-kabel (Item LXV400.99.2R121)
- SC1000 displaymodul (Item LXV402.99.00001)
- SC4500-styrenhet, Prognosys, 5x mA-utgång, 2 digitala givare, 100 - 240 VAC, utan nätsladd (Item LXV525.99A11551)
- SC4500-styrenhet, Claros-kompatibel, 5x mA-utgång, 2 digitala givare, 100 - 240 VAC, utan nätsladd (Item LXV525.99AA1551)
- SC4500-styrenhet, Claros-kompatibel, 5x mA-utgång, 2 digitala givare, 100 - 240 VAC, EU-stickkontakt (Item LXV525.99CA1551)
- SC4500-styrenhet, Prognosys, 5x mA-utgång, 1 digital givare, 100 - 240 VAC, utan nätsladd (Item LXV525.99A11501)
- SC4500-styrenhet, Prognosys, 5x mA-utgång, 2 digitala givare, 24 VDC, utan stickkontakt (Item LXV525.99Z11551)