

Polymetron 9245 Sodium analyser, 1-channel, panel, 1 ppb to 200 ppm Na

Produktnr: **09245=A=1000**

UTGÅNGEN ARTIKEL
Den här artikeln är inte längre tillgänglig.

Process-instrument for the determination of Sodium. Standard (w/o Autocal), panel version. With Kit K. Incl. reagents, maintenance set, installation set and manual.

Automatic electrode reactivation for optimum operation and response time

Easy to install, operate, calibrate and maintain

Adaptable to a variety of conditions

Specifikationer

Analoga utgångar:	4 × (0 or 4) /20 mA [650 Ohms] / linear and dual / Smart
Antal kanaler:	1 Single channel
Antal reläer:	2 programmable (concentration, temperature, minimum sample flow rate)
Depth panel:	252.5 mm
Display :	Digital, 75 × 75 mm graphic with LED backlighting
Europeisk standard för EMC:	Conform EN 61326-1:2006, EN 61010-1:2001
Flöde:	0.2–6 bar (3–87 psi), 5 L/h during sampling phase
Height (panel):	850 mm
Inlopp:	Simple fittings for 6 mm O.D. tubing or 1/4" O.D. in PE-low density
Internationella standarder:	U. L. and GOST Metrology
Kommunikationsmöjligheter:	Standard (4x 4-20 mA outputs)
Matningskrav (Hz):	50 - 60 Hz
Matningskrav (Spänning):	100 - 240 V AC
Mätområde:	1 ppb - 200 ppm with Kit K option
Max. koncentration av suspenderade ämnen i prov:	Below 10 ppm, no oil, no grease. For boiler sample type, install approx. 100 µm filter
Monteringsform:	Panel mount
Omgivningstemperatur:	5 - 50 °C
Parameter:	Sodium
Provtemperatur:	5 - 45°C (41 - 113°F)

Repeatability with DIPA (within a 10° variation):	below 0.02 ppb or 1.5% reading, whichever is greater, within 10 °C variation
Responstid T90:	180 s (t = 90%)
Skyddsklass:	IP 65 (NEMA 4)
Surhetsgrad:	Option K kit (cationic) less than 250 ppm
Utlopp:	Barbed stem for 12 mm (1/2" I.D.) hose
Vikt :	Panel: 18 kg; Enclosure: 23 kg; Full canisters: 2 kg
Width:	450 mm