



EZ7900 Toxicity Analyser

Produktnr: EZ7900.XXXXXXXXXX
SEK Pris: Kontakta oss

Online, automatic respirometry for early warning of toxicity in wastewater treatment plants

Early Warning System against calamities

The EZ7900 Online Toxicity Analyser is able to detect and measure waste water streams that present an acute or chronic toxicity to the biomass of a water treatment plant. This allows operators to take corrective measures to protect the viability of the activated sludge.

Representative measurements on fresh sludge

Measurements are carried out on real sludge freshly sampled from the treatment plant by means of a self-cleaning sampling-filtration system (option). This unique approach has the following advantages: dynamic changes in biomass viability are immediately detected, while sample temperature and pH in the analysis vessel reflects those of the treatment plant.

The EZ7900 Series combine a unique, field-proven respirometric analyser design with a robust sampling-filtration system, assuring detection of toxic compounds or shock loads in an early stage:

- Detection of acute and chronic toxicity on activated sludge
- Measurement of the respiration rate by means of a single dissolved oxygen (DO) sensor
- Smart automatic features
- Standard 4 - 20 mA signal output with alarm processing
- Communication ports supporting connectivity to Modbus
- Multiple stream analysis

There are many additional options available. Please contact Hach for more details.

Specifikationer

Analoga utgångar:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Antal provströmmar:	1, 2, or 4
Automatisk rengöring:	Ja
Certifieringar :	CE compliant / ETL certified
Cykeltid:	10 - 15 minutes
Demineralised water:	N.A.

Detektionsgräns:	N.A.
Digital outputs:	Optional: Modbus (TCP/IP, RS485)
Dimension (H x B x D):	690 mm x 465 mm x 330 mm
Dränering:	Atmospheric pressure, vented, min. Ø 32 mm
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ²
Garanti :	24 månader
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Kalibrering:	Automatic; standard at every analysis cycle
Larm:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Material:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated
Mätmetod:	Respirometry
Matningsspänning:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Mätområde:	0 - 100 % inhibition
Omgivningstemperatur:	10 - 30 °C ±4 °C deviation at 5 - 95% relative humidity (non-condensing)
Parameter:	Toxicity; respiration rate
Precision:	Better than 5% full scale range for standard test solutions
Prov: tryck:	By external overflow vessel
Provflödes hastighet:	100 - 300 mL/min
Provkvalitet:	Maximum particle size 500 µm, < 0.1 g/L
	Most applications require the use of a dual EZ9110 + EZ9120 sampling/filtration system.
Provtemperatur:	10 - 30 °C
Reagent Requirements:	Keep between 10 - 30 °C
Skyddsklass:	Analyser cabinet: IP44 / Panel PC: IP65
Störningar:	N.A.
Vad ingår i leveransen:	EZ7900 Toxicity Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and empty Containers for Reagents with Fittings
Validation:	Automatic; frequency freely programmable
Vikt :	25 kg

Vad finns i förpackningen

EZ7900 Toxicity Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and empty Containers for Reagents with Fittings