



EZ1040 Zinc Zn(II) Analyser

Produktnr: EZ1040.XXXXXXXXXX
SEK Pris: Kontakta oss

Online colorimetric analysis of dissolved Zinc in water

EZ1000 Zinc Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Zinc Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Specifikationer

Analoga utgångar:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Antal provströmmar:	1, 2, 4, or 8
Automatisk rengöring:	Ja
Certifieringar :	CE compliant / ETL certified
Cykeltid:	10 min (dilution + 5 min)
Demineralised water:	For rinsing / dilution
Detektionsgräns:	≤ 10 µg/L
Digital outputs:	Optional: Modbus (TCP/IP, RS485)

Dimension (H x B x D):	690 mm x 465 mm x 330 mm
Dränering:	Atmospheric pressure, vented, min. Ø 32 mm
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ²
Garanti :	24 månader
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Kalibrering:	Automatic, 2-point; frequency freely programmable
Larm:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Material:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated
Mätmetod:	Colorimetric measurement at 630 nm using Zincon, conform with standard method APHA 3500-Zn (B)
Matningsspänning:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Mätområde:	0.05 - 1 mg/L Zn(II)
	Optional:
	0.01 - 0.1 mg/L
	0.025 - 0.25 mg/L
	0.025 - 0.5 mg/L
	0.4 - 4 mg/L (with internal dilution)
	0.8 - 8 mg/L (with internal dilution)
	5 - 100 mg/L (with internal dilution)
Modell:	EZ1040
Omgivningstemperatur:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Parameter:	Zinc
Pausläge:	100 - 240 VAC, 50/60 Hz
Precision:	Better than 2% full scale range for standard test solutions
Prov: tryck:	By external overflow vessel
Provflödes hastighet:	100 - 300 mL/min
Provkvalitet:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Provtemperatur:	10 - 30 °C
Reagent Requirements:	Keep between 10 - 30 °C
Skyddsklass:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65
Störningar:	Aluminium (III) > 5 mg/L, Cadmium (II) > 1 mg/L, Chromate > 50 mg/L, Chromium (III) > 10 mg/L, Cobalt (II) > 30 mg/L, Copper (II) > 30 mg/L, Iron (II) > 9 mg/L, Iron (III) > 7 mg/L, Manganese (II) > 5 mg/L, Nickel (II) > 5 mg/L, organic matter and extreme sample pH fluctuation. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Validation:	Automatic; frequency freely programmable
Vikt :	25 kg